NSN 5340-00-026-0379

Rod End Clevis - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-026-0379

| Thread Class: |
|---|
| 3b rod connection |
| Thread Direction: |
| Right-hand rod connection |
| Thread Length: |
| 1.109 inches rod connection and 1.140 inches rod connection |
| Hole Diameter: |
| Between 0.2497 inches and 0.2507 inches |
| Overall Height: |
| 0.625 inches |
| Overall Width: |
| 0.625 inches |
| End Radius: |
| 0.312 inches |
| Metallic Hardness Rating: |
| 39.0 rockwell c and 45.0 rockwell c |
| Fork Span Width: |
| Between 0.281 inches and 0.286 inches |
| Securing Pin Hole Diameter: |
| Between 0.061 inches and 0.066 inches |
| Distance From Center Of Securing Pin Hole To Rod End: |
| Between 0.251 inches and 0.257 inches |
| Distance From Pivot Pinhole Center To Rod Connection End: |
| 2.375 inches |
| Fork Arm Thickness: |
| 0.171 inches |
| Fork Depth: |
| 0.812 inches |
| Thread Size: |
| 0.375 inches rod connection |
| Material: |
| Steel comp 410 |
| Material Specification: |
| Ams 5612 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2 federal specification single treatment response |
| Style Designator: |
| Clevis |
| Test Data Document: |
| 81349-mil-i-6866 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5340-00-026-0379

Rod End Clevis - Page 2 of 2



| | •• | | • | _ | | |
|---|-----|----|------|--------|------|--------|
| ı | hre | ลด | Seri | 26 I I | PSIU | nator: |
| • | | uu | CCII | | COIG | mator. |

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A264a0