

View Online at <https://aerobasegroup.com/nsn/5340-00-031-6462>

Mounting Hole Type:

Plain

First Leg Length:

0.855 inches

Second Leg Length:

1.131 inches

First Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Hole Diameter:

Between 0.448 inches and 0.458 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.640 inches and 0.660 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.406 inches and 0.469 inches

First Leg Thickness:

Between 0.087 inches and 0.099 inches

Second Leg Thickness:

Between 0.087 inches and 0.099 inches

Center Section Height:

2.503 inches

Center Section Thickness:

Between 0.087 inches and 0.099 inches

First Leg Width:

3.627 inches

First Leg Corner Radius:

Between 0.297 inches and 0.328 inches

First Leg Distance Between Hole Centers Along Width:

3.003 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.297 inches and 0.328 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.297 inches and 0.328 inches

Second Leg End Radius:

Between 0.406 inches and 0.469 inches

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Hardness rockwell c32 to c38

Material:

Steel comp 4130 or steel comp 8630

Material Specification:

Sae4130 assn standard 1st material response or asae8630 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0