

View Online at <https://aerobasegroup.com/nsn/5340-00-031-6462>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.855 inches

**Second Leg Length:**

1.131 inches

**First Leg Hole Diameter:**

Between 0.339 inches and 0.349 inches

**Second Leg Hole Diameter:**

Between 0.448 inches and 0.458 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.640 inches and 0.660 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.406 inches and 0.469 inches

**First Leg Thickness:**

Between 0.087 inches and 0.099 inches

**Second Leg Thickness:**

Between 0.087 inches and 0.099 inches

**Center Section Height:**

2.503 inches

**Center Section Thickness:**

Between 0.087 inches and 0.099 inches

**First Leg Width:**

3.627 inches

**First Leg Corner Radius:**

Between 0.297 inches and 0.328 inches

**First Leg Distance Between Hole Centers Along Width:**

3.003 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.297 inches and 0.328 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.297 inches and 0.328 inches

**Second Leg End Radius:**

Between 0.406 inches and 0.469 inches

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius and tapered

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Special Features:**

Hardness rockwell c32 to c38

**Material:**

Steel comp 4130 or steel comp 8630

**Material Specification:**

Sae4130 assn standard 1st material response or asae8630 assn standard 2nd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0