

View Online at <https://aerobasegroup.com/nsn/5340-00-035-2502>

**Fabrication Method:**

Stamped

**First Leg Length:**

0.750 inches

**Second Leg Length:**

0.782 inches

**Second Leg Width:**

0.750 inches

**First Leg Hole Diameter:**

0.189 inches

**Second Leg Hole Diameter:**

0.281 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.375 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.313 inches

**First Leg Thickness:**

0.051 inches

**Second Leg Thickness:**

0.051 inches

**Center Section Height:**

1.375 inches

**Center Section Width:**

2.250 inches

**Center Section Thickness:**

0.051 inches

**First Leg Width:**

0.750 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance Between Hole Centers Along Width:**

1.031 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.609 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.281 inches

**Second Leg End Radius:**

0.375 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/5, alclad t4 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.