

View Online at <https://aerobasegroup.com/nsn/5340-00-037-8325>

Fabrication Method (non-core):

Machined

First Leg Length:

0.976 inches

Second Leg Length:

2.717 inches

Second Leg Width:

1.562 inches

Second Leg Corner Radius:

0.281 inches

First Leg Hole Diameter:

Between 0.198 inches and 0.204 inches

Second Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Distance Between Hole Centers Along Width:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.281 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.220 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

1.000 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

106.5 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0