

View Online at <https://aerobasegroup.com/nsn/5340-00-054-3628>

First Leg Length:

Between 1.340 inches and 1.400 inches

Second Leg Length:

Between 1.340 inches and 1.400 inches

Second Leg Width:

Between 0.590 inches and 0.650 inches

Second Leg End Width:

0.260 inches

First Leg Hole Diameter:

0.098 inches

Second Leg Hole Diameter:

0.098 inches

Second Leg Distance Between Hole Centers Along Length:

0.590 mils and 0.650 centimeters

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.280 inches and 0.340 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.280 inches and 0.340 inches

First Leg Thickness:

0.032 inches

Second Leg Thickness:

0.032 inches

First Leg Width:

Between 0.590 inches and 0.650 inches

First Leg End Width:

0.260 inches

First Leg Distance Between Hole Centers Along Length:

Between 0.590 inches and 0.650 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.280 inches and 0.340 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.280 inches and 0.340 inches

First Leg Hole Arrangement Style:

Two holes

Second Leg Hole Arrangement Style:

Two holes

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5, alclad o federal specification single material response

Surface Treatment:

Chromate zinc or anodize or chromate

Surface Treatment Specification:

Tt-p-1757 federal specification 1st treatment response or mil-a-8625 military specification 2nd treatment response or mil-c-5541 military specification 3rd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.