## NSN 5340-00-055-9856

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-055-9856

**Fabrication Method (non-core):** 

Machined

First Leg Length:

Between 0.745 inches and 0.755 inches

Second Leg Length:

Between 0.745 inches and 0.755 inches

Second Leg Width:

Between 1.745 inches and 1.755 inches

First Leg Hole Diameter:

Between 0.139 inches and 0.145 inches

Second Leg Hole Diameter:

0.093 inches

Second Leg Distance Between Hole Centers Along Width:

1.156 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:** 

0.250 inches

First Leg Thickness:

Between 0.0469 inches and 0.0781 inches

**Second Leg Thickness:** 

Between 0.0468 inches and 0.0469 inches

First Leg Width:

Between 1.745 inches and 1.755 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.745 inches and 0.755 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.495 inches and 0.505 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.297 inches and 0.329 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

## NSN 5340-00-055-9856

Angle Bracket - Page 2 of 2



N/	late	ria	
IV	alt	:110	и.

Aluminum alloy 6063

**Surface Treatment:** 

Anodize

Style Designator:

Angle

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A042a0