

View Online at <https://aerobasegroup.com/nsn/5340-00-060-2961>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.894 inches and 0.934 inches

**Second Leg Length:**

Between 1.994 inches and 2.024 inches

**Second Leg Width:**

Between 0.594 inches and 0.656 inches

**First Leg Hole Diameter:**

Between 0.339 inches and 0.349 inches

**Second Leg Hole Diameter:**

Between 0.214 inches and 0.224 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.297 inches and 0.320 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.230 inches and 0.240 inches

**First Leg Thickness:**

Between 0.056 inches and 0.068 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.068 inches

**First Leg Width:**

Between 0.594 inches and 0.656 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.297 inches and 0.320 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.300 inches and 0.320 inches

**First Leg End Radius:**

Between 0.469 inches and 0.531 inches

**Second Leg End Radius:**

Between 0.469 inches and 0.531 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 410

**Material Specification:**

Ams 5504 assn standard single material response

**Surface Treatment:**

Passivate

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0