

View Online at <https://aerobasegroup.com/nsn/5340-00-060-3026>

First Leg Length:

1.000 inches

Second Leg Length:

1.250 inches

Second Leg Width:

0.500 inches

First Leg Slot Length:

Between 0.278 inches and 0.288 inches

First Leg Slot Width:

Between 0.200 inches and 0.210 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.211 inches

Second Leg Slot Length:

Between 0.278 inches and 0.288 inches

Second Leg Slot Width:

Between 0.200 inches and 0.210 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.211 inches

First Leg End Radius:

0.500 inches

Second Leg End Radius:

0.500 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Angle

Specification Data:

81343-ms9228-22 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0