# NSN 5340-00-060-3248

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-060-3248

## First Leg Length:

Between 0.582 inches and 0.669 inches

# Second Leg Length:

Between 0.709 inches and 0.792 inches

## Second Leg Width:

Between 0.562 inches and 0.688 inches

#### First Leg Hole Diameter:

Between 0.188 inches and 0.198 inches

#### Second Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

### Second Leg Distance From Edge To Hole Center Along Width:

Between 0.281 inches and 0.344 inches

### Second Leg Distance From Edge To Hole Center Along Length:

Between 0.281 inches and 0.344 inches

#### First Leg Thickness:

Between 0.056 inches and 0.068 inches

## Second Leg Thickness:

Between 0.056 inches and 0.068 inches

#### First Leg Width:

0.500 inches

# First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

### First Leg Distance From Edge To Hole Center Along Length:

Between 0.156 inches and 0.219 inches

### First Leg End Radius:

Between 0.156 inches and 0.219 inches

### Second Leg End Radius:

Between 0.281 inches and 0.344 inches

### First Leg Style:

End radius and tapered

### First Leg Hole Arrangement Style:

One hole

### Second Leg Style:

End radius

### Second Leg Hole Arrangement Style:

One hole

## Second Leg Relationship To First Leg:

Not identical

## First Leg Angle:

90.0 degrees

### **Special Features:**

Heat treatment: quenched and tempered

# NSN 5340-00-060-3248

Angle Bracket - Page 2 of 2



Material:

Steel comp 410

## Material Specification:

Ams 5504 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

### Style Designator:

Angle

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A042a0