

View Online at <https://aerobasegroup.com/nsn/5340-00-061-4218>

**Center To Center Distance Between Bolt Holes Along Width:**

Between 4.865 inches and 4.885 inches

**Center To Center Distance Between Bolt Holes Along Length:**

Between 6.740 inches and 6.760 inches

**Wheel Quantity:**

1

**Safe Operating Load Rating:**

560.0 pounds

**Material And Location:**

Rubber, hard tread

**Unpackaged Unit Weight:**

35.000 pounds

**Wheel Type:**

Built up

**Wheel Diameter:**

8.000 inches

**Effective Height:**

Between 11.000 inches and 11.500 inches

**Features Provided:**

Axle lubrication fitting and swivel lock and swivel lubrication fitting

**Plate Style:**

Rectangular

**Wheel Bearing Type:**

Roller or tapered roller

**Swivel Bearing Type:**

Ball or roller

**Swivel Bearing Arrangement:**

Two row

**Tread Width:**

Between 2.438 inches and 2.562 inches

**Caster Plate Length:**

8.500 inches

**Caster Plate Width:**

7.000 inches

**Caster Plate Mounting Hole Diameter:**

Between 0.652 inches and 0.660 inches

**Style Designator:**

Swivel offset

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A25600