

View Online at <https://aerobasegroup.com/nsn/5340-00-065-9046>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.804 inches and 0.844 inches

**Second Leg Length:**

Between 1.155 inches and 1.195 inches

**Second Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Hole Diameter:**

Between 0.276 inches and 0.286 inches

**Second Leg Hole Diameter:**

Between 0.216 inches and 0.226 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.240 inches and 0.260 inches

**First Leg Thickness:**

Between 0.064 inches and 0.070 inches

**Second Leg Thickness:**

Between 0.064 inches and 0.070 inches

**First Leg Width:**

Between 0.428 inches and 0.448 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.209 inches and 0.229 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.209 inches and 0.229 inches

**First Leg End Radius:**

Between 0.209 inches and 0.229 inches

**Second Leg End Radius:**

Between 0.344 inches and 0.406 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 410

**Material Specification:**

Ams 5504 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fii:**

A042a0