

View Online at <https://aerobasegroup.com/nsn/5340-00-066-8910>

**First Leg Length:**

Between 1.000 inches and 1.040 inches

**Second Leg Length:**

Between 1.150 inches and 1.190 inches

**Second Leg Width:**

Between 0.480 inches and 0.520 inches

**First Leg Hole Diameter:**

Between 0.280 inches and 0.300 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.240 inches and 0.260 inches

**Second Leg Slot Length:**

Between 0.410 inches and 0.440 inches

**Second Leg Slot Width:**

Between 0.190 inches and 0.220 inches

**First Leg Thickness:**

0.050 inches

**Second Leg Thickness:**

0.050 inches

**First Leg Width:**

Between 0.480 inches and 0.520 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.730 inches and 0.750 inches

**First Leg End Radius:**

Between 0.370 inches and 0.430 inches

**Second Leg End Radius:**

Between 0.370 inches and 0.430 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11, t6 federal specification single material response

**Surface Treatment:**

Anodize

**Style Designator:**

Angle

**Fsc Application Data:**

Engine, acft, turbo-prop

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0