

View Online at <https://aerobasegroup.com/nsn/5340-00-066-8910>

First Leg Length:

Between 1.000 inches and 1.040 inches

Second Leg Length:

Between 1.150 inches and 1.190 inches

Second Leg Width:

Between 0.480 inches and 0.520 inches

First Leg Hole Diameter:

Between 0.280 inches and 0.300 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

Second Leg Slot Length:

Between 0.410 inches and 0.440 inches

Second Leg Slot Width:

Between 0.190 inches and 0.220 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

First Leg Width:

Between 0.480 inches and 0.520 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.730 inches and 0.750 inches

First Leg End Radius:

Between 0.370 inches and 0.430 inches

Second Leg End Radius:

Between 0.370 inches and 0.430 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t6 federal specification single material response

Surface Treatment:

Anodize

Style Designator:

Angle

Fsc Application Data:

Engine, acft, turbo-prop

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0