

View Online at <https://aerobasegroup.com/nsn/5340-00-067-9418>

**Thread Class:**

3a rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

0.734 inches rod connection and 0.765 inches rod connection

**Shank Length:**

Between 2.094 inches and 2.125 inches

**Hole Diameter:**

Between 0.312 inches and 0.313 inches

**Shank Diameter:**

Between 0.243 inches and 0.249 inches

**Overall Width:**

Between 0.873 inches and 0.878 inches

**End Radius:**

0.562 inches

**Metallic Hardness Rating:**

33.0 rockwell c and 37.0 rockwell c

**Fork Span Width:**

Between 0.561 inches and 0.566 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

3.562 inches

**Fork Arm Thickness:**

0.156 inches

**Fork Depth:**

1.125 inches

**Thread Size:**

0.312 inches rod connection

**Special Features:**

Shank grooved 0.032 in. Min, 0.036 in. Maximum w, 0.029 in.Min, 0.037 in. Maximum deep, 2.094 in. Min, 2.125 in. Maximum lg

**Material:**

Steel comp 8740

**Material Specification:**

Mil-s-6049 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Gss-8050m, grumman aerospace corporation mfr ref single treatment response

**Style Designator:**

Clevis

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A264a0

**Mil-std (military Standard):**

Mil-s-6049 spec.