

View Online at <https://aerobasegroup.com/nsn/5340-00-069-7587>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.711 inches and 0.774 inches

**Second Leg Length:**

Between 4.031 inches and 4.094 inches

**Second Leg Width:**

Between 2.293 inches and 2.419 inches

**First Leg Hole Diameter:**

Between 0.276 inches and 0.286 inches

**Second Leg Hole Diameter:**

Between 0.214 inches and 0.224 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.281 inches and 0.344 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.281 inches and 0.344 inches

**First Leg Thickness:**

Between 0.045 inches and 0.055 inches

**Second Leg Thickness:**

Between 0.045 inches and 0.055 inches

**First Leg Width:**

Between 1.632 inches and 1.695 inches

**First Leg Corner Radius:**

Between 0.281 inches and 0.344 inches

**First Leg Distance Between Hole Centers Along Width:**

1.351 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.281 inches and 0.344 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.281 inches and 0.344 inches

**Second Leg End Radius:**

Between 0.281 inches and 0.344 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius and tapered

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 410

**Material Specification:**

Ams 5504 assn standard single material response

**Style Designator:**

Offset angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A042a0