

View Online at <https://aerobasegroup.com/nsn/5340-00-069-7587>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.711 inches and 0.774 inches

Second Leg Length:

Between 4.031 inches and 4.094 inches

Second Leg Width:

Between 2.293 inches and 2.419 inches

First Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.281 inches and 0.344 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.281 inches and 0.344 inches

First Leg Thickness:

Between 0.045 inches and 0.055 inches

Second Leg Thickness:

Between 0.045 inches and 0.055 inches

First Leg Width:

Between 1.632 inches and 1.695 inches

First Leg Corner Radius:

Between 0.281 inches and 0.344 inches

First Leg Distance Between Hole Centers Along Width:

1.351 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.281 inches and 0.344 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.281 inches and 0.344 inches

Second Leg End Radius:

Between 0.281 inches and 0.344 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Offset angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0