NSN 5340-00-070-2626

Double Angle Bracket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-00-070-2626

| Filtrate Materials |
|---|
| Fabrication Method (non-core): |
| Machined |
| First Leg Hole Diameter: |
| Between 0.214 inches and 0.224 inches |
| First Leg Thickness: |
| Between 0.056 inches and 0.068 inches |
| Second Leg Thickness: |
| Between 0.056 inches and 0.068 inches |
| Center Section Width: |
| Between 0.485 inches and 0.515 inches |
| Center Section Thickness: |
| Between 0.056 inches and 0.068 inches |
| First Leg Width: |
| Between 0.485 inches and 0.515 inches |
| First Leg Distance From Edge To Hole Center Along Width: |
| Between 0.240 inches and 0.260 inches |
| First Leg Distance From Edge To Hole Center Along Length: |
| Between 0.240 inches and 0.260 inches |
| First Leg End Radius: |
| Between 0.344 inches and 0.406 inches |
| First Leg Style: |
| End radius |
| First Leg Hole Arrangement Style: |
| One hole |
| Second Leg Relationship To First Leg: |
| Identical |
| Material: |
| Titanium alloy |
| Material Specification: |
| Ams 4910 assn standard single material response |
| Style Designator: |
| Double angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| <u></u> |
| Demilitarization: |
| No |
| Fiig: |
| A042a0 |