

View Online at <https://aerobasegroup.com/nsn/5340-00-071-9190>

Mounting Hole Type:

Counterbored

First Leg Length:

1.250 inches

Second Leg Length:

1.250 inches

Second Leg Width:

1.310 inches

First Leg Hole Diameter:

Between 0.281 inches and 0.312 inches

Second Leg Hole Diameter:

Between 0.109 inches and 0.281 inches

Second Leg Distance Between Hole Centers Along Width:

0.188 inches

Second Leg Distance Between Hole Centers Along Length:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.472 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

1.310 inches

First Leg Distance Between Hole Centers Along Width:

0.750 inches

First Leg Distance Between Hole Centers Along Length:

0.312 inches

First Leg Distance From Edge To Hole Center Along Width:

0.280 inches

First Leg Distance From Edge To Hole Center Along Length:

0.278 inches

Second Leg End Radius:

Between 0.750 inches and 1.000 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200/5 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.