

View Online at <https://aerobasegroup.com/nsn/5340-00-073-1603>

Fabrication Method (non-core):

Machined

First Leg Length:

0.750 inches

Second Leg Length:

2.650 inches

Second Leg Width:

1.660 inches

First Leg Hole Diameter:

Between 0.343 inches and 0.369 inches

Second Leg Hole Diameter:

Between 0.218 inches and 0.229 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.820 inches and 0.840 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 1.250 inches and 1.270 inches

First Leg Thickness:

0.060 inches

Second Leg Thickness:

0.060 inches

First Leg Width:

1.660 inches

First Leg Corner Radius:

0.310 inches

First Leg Distance Between Hole Centers Along Width:

Between 1.030 inches and 1.050 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.300 inches and 0.320 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.300 inches and 0.320 inches

Second Leg End Radius:

0.500 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 301

Material Specification:

Mil-s-5059 military specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-s-5059 spec.