

View Online at <https://aerobasegroup.com/nsn/5340-00-074-9950>

**Shoulder Diameter:**

Between 0.800 inches and 0.805 inches

**Body Width:**

0.875 inches

**Shank Outside Diameter:**

Between 0.555 inches and 0.565 inches

**Tongue Width:**

2.188 inches

**Tongue Thickness:**

Between 0.802 inches and 0.812 inches

**Rod Connection Bore Diameter:**

0.380 inches

**Securing Pin Hole Diameter:**

0.094 inches

**Rod Connection Bore Depth:**

4.500 inches

**Distance From Center Of Securing Pin Hole To Rod End:**

6.750 inches

**Shanklength:**

5.960 inches

**Distance From End To Hole Center:**

8.490 inches

**Special Features:**

Shank end slotted 0.186 in. W by 1.190 in. Lg; shank shoulder grooved 0.124 in. W

**Material:**

Steel comp 630

**Material Specification:**

Ams 5643 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Pv-f-5, the boeing co mfr ref single treatment response

**Test Data Document:**

77272-bac5424 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A264a0