

View Online at <https://aerobasegroup.com/nsn/5340-00-074-9950>

Shoulder Diameter:

Between 0.800 inches and 0.805 inches

Body Width:

0.875 inches

Shank Outside Diameter:

Between 0.555 inches and 0.565 inches

Tongue Width:

2.188 inches

Tongue Thickness:

Between 0.802 inches and 0.812 inches

Rod Connection Bore Diameter:

0.380 inches

Securing Pin Hole Diameter:

0.094 inches

Rod Connection Bore Depth:

4.500 inches

Distance From Center Of Securing Pin Hole To Rod End:

6.750 inches

Shanklength:

5.960 inches

Distance From End To Hole Center:

8.490 inches

Special Features:

Shank end slotted 0.186 in. W by 1.190 in. Lg; shank shoulder grooved 0.124 in. W

Material:

Steel comp 630

Material Specification:

Ams 5643 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Pv-f-5, the boeing co mfr ref single treatment response

Test Data Document:

77272-bac5424 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A264a0