

View Online at <https://aerobasegroup.com/nsn/5340-00-075-2673>

Fabrication Method (non-core):

Machined

First Leg Length:

0.920 inches

Second Leg Length:

1.930 inches

Second Leg Width:

1.460 inches

First Leg Hole Diameter:

0.344 inches

Second Leg Hole Diameter:

0.219 inches

Second Leg Distance Between Hole Centers Along Length:

0.900 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.380 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Thickness:

0.043 inches

Second Leg Thickness:

0.043 inches

First Leg Width:

1.460 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

0.960 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

Second Leg End Radius:

0.380 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

95.0 degrees

Material:

Steel comp 4130

Material Specification:

Ams 6350 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0