

View Online at <https://aerobasegroup.com/nsn/5340-00-075-4002>

Fabrication Method (non-core):

Stamped

First Leg Length:

Between 0.765 inches and 0.848 inches

Second Leg Length:

Between 1.110 inches and 1.192 inches

Second Leg Width:

Between 1.452 inches and 1.576 inches

Second Leg Corner Radius:

Between 0.250 inches and 0.312 inches

First Leg Hole Diameter:

Between 0.214 inches and 0.225 inches

Second Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Distance Between Hole Centers Along Width:

0.952 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.250 inches and 0.312 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.250 inches and 0.312 inches

First Leg Thickness:

Between 0.045 inches and 0.055 inches

Second Leg Thickness:

Between 0.045 inches and 0.055 inches

First Leg Width:

Between 0.604 inches and 0.634 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.375 inches and 0.438 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.375 inches and 0.438 inches

First Leg End Radius:

Between 0.375 inches and 0.438 inches

First Leg Style:

End radius and tapered

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0