

View Online at <https://aerobasegroup.com/nsn/5340-00-075-4892>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.893 inches and 0.903 inches

First Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Distance Between Hole Centers Along Width:

1.309 inches

Second Leg Distance Between Hole Centers Along Length:

0.350 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.281 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.281 inches

First Leg Thickness:

Between 0.045 inches and 0.055 inches

Second Leg Thickness:

Between 0.045 inches and 0.055 inches

First Leg Width:

2.850 inches

First Leg Corner Radius:

0.375 inches

First Leg Distance Between Hole Centers Along Width:

1.400 inches

First Leg Distance From Edge To Hole Center Along Width:

0.800 inches

First Leg Distance From Edge To Hole Center Along Length:

0.375 inches

Second Leg End Radius:

0.281 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

100.0 degrees

Material:

Steel comp 4130

Material Specification:

Ams 6350 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0