

View Online at <https://aerobasegroup.com/nsn/5340-00-075-4897>

Fabrication Method (non-core):

Machined

First Leg Length:

0.640 inches

Second Leg Length:

1.470 inches

Second Leg Width:

1.570 inches

Second Leg Corner Radius:

0.310 inches

First Leg Hole Diameter:

Between 0.193 inches and 0.198 inches

Second Leg Hole Diameter:

Between 0.338 inches and 0.345 inches

Second Leg Distance Between Hole Centers Along Width:

0.950 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.310 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Thickness:

0.060 inches

Second Leg Thickness:

0.060 inches

First Leg Width:

0.970 inches

First Leg Distance From Edge To Hole Center Along Width:

0.670 inches

First Leg Distance From Edge To Hole Center Along Length:

0.300 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

First Leg Angle:

90.0 degrees

Material:

Steel comp 301

Material Specification:

Mil-s-5059 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Offset angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-5059 spec.