

View Online at <https://aerobasegroup.com/nsn/5340-00-075-4898>

Fabrication Method (non-core):

Machined

Second Leg Length:

0.900 inches

Second Leg Width:

1.300 inches

First Leg Hole Diameter:

Between 0.345 inches and 0.350 inches

Second Leg Hole Diameter:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Thickness:

0.160 inches

Second Leg Thickness:

0.160 inches

First Leg Width:

2.539 inches

First Leg Corner Radius:

0.310 inches

First Leg Distance Between Lower Hole Centers Along Width:

1.919 inches

First Leg Distance Between Hole Centers Along Length:

0.031 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.959 inches

First Leg Distance From Edge To Hole Center Along Width:

0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

0.310 inches

Second Leg End Radius:

0.380 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

159.0 degrees

Special Features:

Right hand

Material:

Steel comp 4130

Material Specification:

Mil-s-18729 military specification single material response

Surface Treatment:

Paint

Style Designator:

Offset angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-18729 spec.