

View Online at <https://aerobasegroup.com/nsn/5340-00-075-4899>

Fabrication Method (non-core):

Machined

First Leg Length:

0.900 inches

Second Leg Length:

1.631 inches

End Application:

W/s: engine, aircraft, tf-33-p-7 (c-141a/b)

Second Leg Width:

1.300 inches

Second Leg Corner Radius:

0.281 inches

First Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.857 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.884 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.374 inches

First Leg Thickness:

0.160 inches

Second Leg Thickness:

0.160 inches

First Leg Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.375 inches

First Leg Distance From Edge To Hole Center Along Length:

0.375 inches

First Leg End Radius:

0.375 inches

Second Leg End Radius:

0.380 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

159.0 degrees

Special Features:

Left hand

Material:

Steel comp 4130 or steel comp 8630

Material Specification:

Ams 6350 assn standard 1st material response or ams 6355 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0