

View Online at <https://aerobasegroup.com/nsn/5340-00-075-4903>

Fabrication Method (non-core):

Stamped

Mounting Hole Type:

Plain

First Leg Length:

Between 0.709 inches and 0.791 inches

Second Leg Length:

Between 0.709 inches and 0.791 inches

First Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.219 inches and 0.281 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.219 inches and 0.281 inches

First Leg Thickness:

Between 0.045 inches and 0.055 inches

Second Leg Thickness:

Between 0.045 inches and 0.055 inches

Center Section Thickness:

Between 0.045 inches and 0.055 inches

First Leg Width:

Between 1.919 inches and 1.981 inches

First Leg Corner Radius:

Between 0.219 inches and 0.281 inches

First Leg Distance Between Hole Centers Along Width:

1.700 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.219 inches and 0.281 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.219 inches and 0.281 inches

Second Leg End Radius:

Between 0.219 inches and 0.281 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

Material:

Steel

Material Specification:

Ams2400 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0