

View Online at <https://aerobasegroup.com/nsn/5340-00-075-4903>

**Fabrication Method (non-core):**

Stamped

**Mounting Hole Type:**

Plain

**First Leg Length:**

Between 0.709 inches and 0.791 inches

**Second Leg Length:**

Between 0.709 inches and 0.791 inches

**First Leg Hole Diameter:**

Between 0.276 inches and 0.286 inches

**Second Leg Hole Diameter:**

Between 0.214 inches and 0.224 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.219 inches and 0.281 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.219 inches and 0.281 inches

**First Leg Thickness:**

Between 0.045 inches and 0.055 inches

**Second Leg Thickness:**

Between 0.045 inches and 0.055 inches

**Center Section Thickness:**

Between 0.045 inches and 0.055 inches

**First Leg Width:**

Between 1.919 inches and 1.981 inches

**First Leg Corner Radius:**

Between 0.219 inches and 0.281 inches

**First Leg Distance Between Hole Centers Along Width:**

1.700 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.219 inches and 0.281 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.219 inches and 0.281 inches

**Second Leg End Radius:**

Between 0.219 inches and 0.281 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius and tapered

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**Material:**

Steel

**Material Specification:**

Ams2400 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0