

View Online at <https://aerobasegroup.com/nsn/5340-00-075-4906>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.771 inches and 0.854 inches

**Second Leg Length:**

Between 0.930 inches and 0.970 inches

**Second Leg Width:**

Between 0.752 inches and 0.898 inches

**First Leg Hole Diameter:**

Between 0.214 inches and 0.224 inches

**Second Leg Hole Diameter:**

Between 0.276 inches and 0.286 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.471 inches and 0.554 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.240 inches and 0.260 inches

**First Leg Thickness:**

Between 0.045 inches and 0.055 inches

**Second Leg Thickness:**

Between 0.045 inches and 0.055 inches

**First Leg Width:**

Between 0.562 inches and 0.688 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.281 inches and 0.344 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.281 inches and 0.344 inches

**First Leg End Radius:**

Between 0.281 inches and 0.344 inches

**Second Leg End Radius:**

Between 0.281 inches and 0.344 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Ams 6350 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Offset angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A042a0