

View Online at <https://aerobasegroup.com/nsn/5340-00-075-4906>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.771 inches and 0.854 inches

Second Leg Length:

Between 0.930 inches and 0.970 inches

Second Leg Width:

Between 0.752 inches and 0.898 inches

First Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.471 inches and 0.554 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

Between 0.045 inches and 0.055 inches

Second Leg Thickness:

Between 0.045 inches and 0.055 inches

First Leg Width:

Between 0.562 inches and 0.688 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.281 inches and 0.344 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.281 inches and 0.344 inches

First Leg End Radius:

Between 0.281 inches and 0.344 inches

Second Leg End Radius:

Between 0.281 inches and 0.344 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 4130

Material Specification:

Ams 6350 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Offset angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0