

View Online at <https://aerobasegroup.com/nsn/5340-00-075-4912>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.952 inches and 0.972 inches

Second Leg Length:

Between 1.299 inches and 1.351 inches

Second Leg Width:

Between 1.539 inches and 1.663 inches

First Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.359 inches and 0.391 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.239 inches and 0.250 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

Between 1.289 inches and 1.351 inches

First Leg Corner Radius:

Between 0.250 inches and 0.312 inches

First Leg Distance Between Hole Centers Along Width:

1.039 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.250 inches and 0.312 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.250 inches and 0.312 inches

Second Leg End Radius:

Between 0.359 inches and 0.391 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0