

View Online at <https://aerobasegroup.com/nsn/5340-00-075-4919>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.744 inches and 0.826 inches

Second Leg Length:

Between 1.541 inches and 1.624 inches

Second Leg Width:

Between 1.853 inches and 1.916 inches

Second Leg Corner Radius:

Between 0.281 inches and 0.344 inches

First Leg Hole Diameter:

Between 0.245 inches and 0.255 inches

Second Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Distance Between Hole Centers Along Width:

1.572 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.281 inches and 0.344 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.281 inches and 0.344 inches

First Leg Thickness:

Between 0.045 inches and 0.056 inches

Second Leg Thickness:

Between 0.045 inches and 0.056 inches

First Leg Width:

Between 1.688 inches and 1.812 inches

First Leg Corner Radius:

Between 0.344 inches and 0.406 inches

First Leg Distance Between Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.344 inches and 0.406 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.344 inches and 0.406 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 4130 or steel comp 8630

Material Specification:

Ams 6350 assn standard 1st material response or ams 6355 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0