

View Online at <https://aerobasegroup.com/nsn/5340-00-075-6052>

First Leg Length:

Between 0.884 inches and 0.966 inches

Second Leg Length:

Between 1.293 inches and 1.333 inches

Second Leg Width:

5.568 mils and 5.608 centimeters

Second Leg Corner Radius:

Between 0.344 inches and 0.406 inches

First Leg Hole Diameter:

0.214 mils and 0.224 centimeters

Second Leg Hole Diameter:

0.339 mils and 0.349 centimeters

Second Leg Distance Between Lower Hole Centers Along Width:

4.962 inches

Second Leg Distance Between Hole Centers Along Length:

0.279 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

2.532 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.303 mils and 0.323 centimeters

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.303 inches and 0.323 inches

First Leg Thickness:

Between 0.045 inches and 0.055 inches

Second Leg Thickness:

Between 0.045 inches and 0.055 inches

First Leg Corner Radius:

Between 0.344 inches and 0.406 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.700 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

2.200 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.344 inches and 0.406 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Three holes

First Leg Angle:

90.0 degrees

Material:

Steel comp 4130 or steel comp 8630

Material Specification:

Ams 6350 assn standard 1st material response or ams 6355 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0