

View Online at <https://aerobasegroup.com/nsn/5340-00-075-6052>

**First Leg Length:**

Between 0.884 inches and 0.966 inches

**Second Leg Length:**

Between 1.293 inches and 1.333 inches

**Second Leg Width:**

5.568 mils and 5.608 centimeters

**Second Leg Corner Radius:**

Between 0.344 inches and 0.406 inches

**First Leg Hole Diameter:**

0.214 mils and 0.224 centimeters

**Second Leg Hole Diameter:**

0.339 mils and 0.349 centimeters

**Second Leg Distance Between Lower Hole Centers Along Width:**

4.962 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.279 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

2.532 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.303 mils and 0.323 centimeters

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.303 inches and 0.323 inches

**First Leg Thickness:**

Between 0.045 inches and 0.055 inches

**Second Leg Thickness:**

Between 0.045 inches and 0.055 inches

**First Leg Corner Radius:**

Between 0.344 inches and 0.406 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

1.700 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

2.200 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.344 inches and 0.406 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Three holes

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 4130 or steel comp 8630

**Material Specification:**

Ams 6350 assn standard 1st material response or ams 6355 assn standard 2nd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0