

View Online at <https://aerobasegroup.com/nsn/5340-00-075-6053>

**Fabrication Method (non-core):**

Machined

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.150 inches

**Second Leg Length:**

1.300 inches

**First Leg Hole Diameter:**

Between 0.245 inches and 0.255 inches

**Second Leg Hole Diameter:**

Between 0.339 inches and 0.349 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.336 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.338 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.825 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.312 inches

**First Leg Thickness:**

Between 0.055 inches and 0.069 inches

**Second Leg Thickness:**

Between 0.055 inches and 0.069 inches

**First Leg Width:**

4.250 inches

**First Leg Corner Radius:**

0.375 inches

**First Leg Distance Between Hole Centers Along Width:**

3.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.375 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.375 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

79.0 degrees

**Material:**

Steel comp 4130 or steel comp 8630

**Material Specification:**

Ams 6350 assn standard 1st material response or ams 6355 assn standard 2nd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0