

View Online at <https://aerobasegroup.com/nsn/5340-00-075-6053>

Fabrication Method (non-core):

Machined

Mounting Hole Type:

Plain

First Leg Length:

1.150 inches

Second Leg Length:

1.300 inches

First Leg Hole Diameter:

Between 0.245 inches and 0.255 inches

Second Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Distance Between Hole Centers Along Width:

2.336 inches

Second Leg Distance Between Hole Centers Along Length:

0.338 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.825 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.312 inches

First Leg Thickness:

Between 0.055 inches and 0.069 inches

Second Leg Thickness:

Between 0.055 inches and 0.069 inches

First Leg Width:

4.250 inches

First Leg Corner Radius:

0.375 inches

First Leg Distance Between Hole Centers Along Width:

3.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.375 inches

First Leg Distance From Edge To Hole Center Along Length:

0.375 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

79.0 degrees

Material:

Steel comp 4130 or steel comp 8630

Material Specification:

Ams 6350 assn standard 1st material response or ams 6355 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0