

View Online at <https://aerobasegroup.com/nsn/5340-00-076-0050>

Cross Sectional Shape:

Square or rectangular recess

Hole Diameter:

0.516 inches

Width:

Between 4.438 inches and 4.500 inches

Flange Thickness:

0.500 inches

Edge Shape:

Rectangle, four holes

Length:

Between 4.438 inches and 4.500 inches

Inside Width:

Between 3.873 inches and 3.874 inches

Inside Length:

Between 3.873 inches and 3.874 inches

Corner Radius:

0.500 inches

Distance Between Holes Along Length:

3.500 inches

Distance Between Holes Along Width:

3.500 inches

Distance From First Hole Centerline To End Along Length:

0.500 inches

Distance From First Hole Centerline To End Along Width:

0.500 inches

First Recess Inside Height:

0.706 inches

Inside Corner Radius:

0.016 inches

Body Thickness:

0.356 inches

Securing Device Type:

Threaded fastener

Mounting Opening Shape Style:

Unthreaded hole

Material:

Steel

Material Specification:

Qq-s-681, class 2 federal specification single material response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Mil-p-16232, type 2, class 1 military specification single treatment response

Fsc Application Data:

Miscellaneous vehicular components

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A531c0

Mil-std (military Standard):

Mil-p-16232 spec.