

View Online at <https://aerobasegroup.com/nsn/5340-00-076-7218>

**Thread Class:**

3b rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

0.440 inches rod connection

**Shank Length:**

Between 0.550 inches and 0.610 inches

**Hole Diameter:**

Between 0.190 inches and 0.196 inches

**Overall Height:**

Between 0.470 inches and 0.530 inches

**Overall Width:**

Between 0.225 inches and 0.270 inches

**End Radius:**

Between 0.220 inches and 0.280 inches

**Fork Span Width:**

Between 0.135 inches and 0.140 inches

**Securing Pin Hole Diameter:**

Between 0.052 inches and 0.072 inches

**Distance From Center Of Securing Pin Hole To Rod End:**

Between 0.150 inches and 0.210 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

Between 1.150 inches and 1.210 inches

**Fork Arm Thickness:**

Between 0.045 inches and 0.065 inches

**Fork Depth:**

Between 0.570 inches and 0.630 inches

**Thread Size:**

0.190 inches rod connection

**Material:**

Aluminum alloy 2024 and aluminum alloy 356.0

**Material Specification:**

Qq-a-225/6, t4 federal specification single material response and ams 4260 assn standard single material response

**Surface Treatment:**

Oxide film and chromate zinc

**Surface Treatment Specification:**

Bps, fw4182, bell helicopter co mfr ref single treatment response and mil-p-8585-canceled military specification single treatment response

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A264a0

**Mil-std (military Standard):**

Mil-p-8585-canceled spec.