

View Online at <https://aerobasegroup.com/nsn/5340-00-076-7218>

Thread Class:

3b rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

0.440 inches rod connection

Shank Length:

Between 0.550 inches and 0.610 inches

Hole Diameter:

Between 0.190 inches and 0.196 inches

Overall Height:

Between 0.470 inches and 0.530 inches

Overall Width:

Between 0.225 inches and 0.270 inches

End Radius:

Between 0.220 inches and 0.280 inches

Fork Span Width:

Between 0.135 inches and 0.140 inches

Securing Pin Hole Diameter:

Between 0.052 inches and 0.072 inches

Distance From Center Of Securing Pin Hole To Rod End:

Between 0.150 inches and 0.210 inches

Distance From Pivot Pinhole Center To Rod Connection End:

Between 1.150 inches and 1.210 inches

Fork Arm Thickness:

Between 0.045 inches and 0.065 inches

Fork Depth:

Between 0.570 inches and 0.630 inches

Thread Size:

0.190 inches rod connection

Material:

Aluminum alloy 2024 and aluminum alloy 356.0

Material Specification:

Qq-a-225/6, t4 federal specification single material response and ams 4260 assn standard single material response

Surface Treatment:

Oxide film and chromate zinc

Surface Treatment Specification:

Bps, fw4182, bell helicopter co mfr ref single treatment response and mil-p-8585-canceled military specification single treatment response

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A264a0

Mil-std (military Standard):

Mil-p-8585-canceled spec.