NSN 5340-00-078-2902

Access Cover - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-00-078-2902

Flat Width: 41.380 inches Edge Shape: Rectangle, no holes Length: 20.620 inches Securing Device Type: Elbow catch Special Features: With two gr(b handles, 8.310 in. O/a lg, 1.780 in. O/a h, with four mtg holes each, 0.250 @min 0.312 maximum in. Dia, 7.000 in. C distance between bolt holes along the lg, 0.980 min 1.020 maximum in. C to c distance between @bolt holes along the w, steel, aid 1008-1030, 1.940 in. O/a w Material: Steel Surface Treatment Specification: Astm a368 assn standard single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No	oss Sectional Shape:
41.380 inches Edge Shape: Rectangle, no holes Length: 20.620 inches Securing Device Type: Elbow catch Special Features: With two gr(b handles, 8.310 in. O/a lg, 1.780 in. O/a h, with four mtg holes each, 0.250 @min 0.312 maximum in. Dia, 7.000 in. C distance between bolt holes along the lg, 0.980 min 1.020 maximum in. C to c distance between @bolt holes along the w, steel, aid 1008-1030, 1.940 in. O/a w Material: Steel Surface Treatment Specification: Astm a368 assn standard single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:	at .
Edge Shape: Rectangle, no holes Length: 20.620 inches Securing Device Type: Elbow catch Special Features: With two gr(b handles, 8.310 in. O/a lg, 1.780 in. O/a h, with four mtg holes each, 0.250 @min 0.312 maximum in. Dia, 7.000 in. C distance between bolt holes along the lg, 0.980 min 1.020 maximum in. C to c distance between @bolt holes along the w, steel, aid 1008-1030, 1.940 in. O/a w Material: Steel Surface Treatment Specification: Astm a368 assn standard single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:	dth:
Rectangle, no holes Length: 20.620 inches Securing Device Type: Elbow catch Special Features: With two gr(b handles, 8.310 in. O/a lg, 1.780 in. O/a h, with four mtg holes each, 0.250 @min 0.312 maximum in. Dia, 7.000 in. C distance between bolt holes along the lg, 0.980 min 1.020 maximum in. C to c distance between @bolt holes along the w, steel, ais 1008-1030, 1.940 in. O/a w Material: Steel Surface Treatment Specification: Astm a368 assn standard single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:	.380 inches
Length: 20.620 inches Securing Device Type: Elbow catch Special Features: With two gr(b handles, 8.310 in. O/a lg, 1.780 in. O/a h, with four mtg holes each, 0.250 @min 0.312 maximum in. Dia, 7.000 in. C distance between bolt holes along the lg, 0.980 min 1.020 maximum in. C to c distance between @bolt holes along the w, steel, ais 1008-1030, 1.940 in. O/a w Material: Steel Surface Treatment Specification: Astm a368 assn standard single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:	ge Shape:
20.620 inches Securing Device Type: Elbow catch Special Features: With two gr(b handles, 8.310 in. O/a lg, 1.780 in. O/a h, with four mtg holes each, 0.250 @min 0.312 maximum in. Dia, 7.000 in. C distance between bolt holes along the lg, 0.980 min 1.020 maximum in. C to c distance between @bolt holes along the w, steel, ais 1008-1030, 1.940 in. O/a w Material: Steel Surface Treatment Specification: Astm a368 assn standard single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:	ctangle, no holes
Securing Device Type: Elbow catch Special Features: With two gr(b handles, 8.310 in. O/a lg, 1.780 in. O/a h, with four mtg holes each, 0.250 @min 0.312 maximum in. Dia, 7.000 in. C distance between bolt holes along the lg, 0.980 min 1.020 maximum in. C to c distance between @bolt holes along the w, steel, ais 1008-1030, 1.940 in. O/a w Material: Steel Surface Treatment Specification: Astm a368 assn standard single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:	ngth:
Elbow catch Special Features: With two gr(b handles, 8.310 in. O/a lg, 1.780 in. O/a h, with four mtg holes each, 0.250 @min 0.312 maximum in. Dia, 7.000 in. C distance between bolt holes along the lg, 0.980 min 1.020 maximum in. C to c distance between @bolt holes along the w, steel, ais 1008-1030, 1.940 in. O/a w Material: Steel Surface Treatment Specification: Astm a368 assn standard single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:	.620 inches
Special Features: With two gr(b handles, 8.310 in. O/a lg, 1.780 in. O/a h, with four mtg holes each, 0.250 @min 0.312 maximum in. Dia, 7.000 in. C distance between bolt holes along the lg, 0.980 min 1.020 maximum in. C to c distance between @bolt holes along the w, steel, ais 1008-1030, 1.940 in. O/a w Material: Steel Surface Treatment Specification: Astm a368 assn standard single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:	curing Device Type:
With two gr(b handles, 8.310 in. O/a lg, 1.780 in. O/a h, with four mtg holes each, 0.250 @min 0.312 maximum in. Dia, 7.000 in. C distance between bolt holes along the lg, 0.980 min 1.020 maximum in. C to c distance between @bolt holes along the w, steel, ais 1008-1030, 1.940 in. O/a w Material: Steel Surface Treatment Specification: Astm a368 assn standard single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:	pow catch
distance between bolt holes along the Ig, 0.980 min 1.020 maximum in. C to c distance between @bolt holes along the w, steel, ais 1008-1030, 1.940 in. O/a w Material: Steel Surface Treatment Specification: Astm a368 assn standard single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:	ecial Features:
Material: Steel Surface Treatment Specification: Astm a368 assn standard single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:	th two gr(b handles, 8.310 in. O/a lg, 1.780 in. O/a h, with four mtg holes each, 0.250 @min 0.312 maximum in. Dia, 7.000 in. C to c
Material: Steel Surface Treatment Specification: Astm a368 assn standard single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:	tance between bolt holes along the Ig, 0.980 min 1.020 maximum in. C to c distance between @bolt holes along the w, steel, aisi
Steel Surface Treatment Specification: Astm a368 assn standard single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:	08-1030, 1.940 in. O/a w
Surface Treatment Specification: Astm a368 assn standard single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:	nterial:
Astm a368 assn standard single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:	eel
Shelf Life: N/a Unit Of Measure: Demilitarization:	rface Treatment Specification:
N/a Unit Of Measure: Demilitarization:	tm a368 assn standard single treatment response
Unit Of Measure: Demilitarization:	elf Life:
Demilitarization:	a
	it Of Measure:
No	militarization:
Fiig:	g:
A531c0	31c0