

View Online at <https://aerobasegroup.com/nsn/5340-00-079-4941>

Fabrication Method (non-core):

Stamped

First Leg Length:

Between 0.792 inches and 0.832 inches

Second Leg Length:

Between 1.042 inches and 1.082 inches

Second Leg Width:

Between 0.615 inches and 0.635 inches

First Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.307 inches and 0.317 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.302 inches and 0.322 inches

First Leg Thickness:

Between 0.045 inches and 0.055 inches

Second Leg Thickness:

Between 0.045 inches and 0.055 inches

First Leg Width:

Between 0.615 inches and 0.635 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.307 inches and 0.317 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.302 inches and 0.322 inches

First Leg End Radius:

Between 0.469 inches and 0.531 inches

Second Leg End Radius:

Between 0.469 inches and 0.531 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0