

View Online at <https://aerobasegroup.com/nsn/5340-00-080-7574>

First Leg Length:

2.750 inches

Second Leg Length:

4.688 inches

Second Leg Width:

5.000 inches

First Leg Hole Diameter:

0.625 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.438 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.438 inches

Second Leg Slot Length:

1.266 inches

Second Leg Slot Width:

Between 0.760 inches and 0.770 inches

First Leg Thickness:

Between 0.719 inches and 0.781 inches

Second Leg Thickness:

Between 0.969 inches and 1.031 inches

First Leg Width:

5.000 inches

First Leg Distance Between Hole Centers Along Width:

3.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.875 inches

First Leg Distance From Edge To Hole Center Along Length:

0.875 inches

Second Leg End Radius:

1.438 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

45.0 degrees

Material:

Aluminum alloy

Material Specification:

Mil-a-19005 military specification all material responses

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, ty3, cl1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-a-19005 spec.