

View Online at <https://aerobasegroup.com/nsn/5340-00-081-1727>

Fabrication Method (non-core):

Stamped

First Leg Length:

0.359 inches

Second Leg Length:

0.531 inches

Second Leg Width:

Between 0.302 inches and 0.322 inches

First Leg Hole Diameter:

0.156 inches

Second Leg Hole Diameter:

Between 0.192 inches and 0.193 inches

Second Leg Distance Between Hole Centers Along Length:

Between 0.182 inches and 0.192 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.146 inches and 0.166 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.094 inches

First Leg Thickness:

0.032 inches

Second Leg Thickness:

0.032 inches

First Leg Width:

Between 0.302 inches and 0.322 inches

First Leg Distance From Edge To Hole Center Along Width:

0.156 inches

First Leg Distance From Edge To Hole Center Along Length:

0.156 inches

First Leg End Radius:

0.156 inches

Second Leg End Radius:

0.156 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Heat Treatment:

H-32 strain hardened

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

580-0036-00 fscm 13499 mfr ref single treatment response

Style Designator:

Angle

Fsc Application Data:

Radio sets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0