

View Online at <https://aerobasegroup.com/nsn/5340-00-081-3933>

Wheel Quantity:

1

Stem Style:

Gripneck

Stem Length:

1.438 inches

Stem Diameter:

0.375 inches

Material And Location:

Steel body

Surface Treatment And Location:

Copper, oxidized body

Wheel Type:

Built up

Wheel Diameter:

2.000 inches

Stem Socket Style:

Gripneck-open type

Wheel Bearing Type:

Plain, self-lubricated

Swivel Bearing Type:

Annular ball

Swivel Bearing Arrangement:

Two row

Stem Socket Depth:

1.500 inches

Stem Socket Diameter:

0.375 inches

Special Features:

Nonstaining, nonmarking cushion treads, permanently bonded, impact resistant, hard rubber composition core; wheels tread thickness 3/16in.; wheel tread and core material hardness range hard rubber 75-85 shore d, soft rubber 70-85 shore a; tensile 1500 psi min., adhesion between tread and core is 50 lbs per inch of width; axles and stems - cold drawn steel, nut and bolt combination or solid rivet type and permanently fastened; ball bearings - corrosion resistant, case hardened ground steel, assembly with a water repellent grease

Style Designator:

Swivel offset

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A25600