

View Online at <https://aerobasegroup.com/nsn/5340-00-081-3933>

**Wheel Quantity:**

1

**Stem Style:**

Gripneck

**Stem Length:**

1.438 inches

**Stem Diameter:**

0.375 inches

**Material And Location:**

Steel body

**Surface Treatment And Location:**

Copper, oxidized body

**Wheel Type:**

Built up

**Wheel Diameter:**

2.000 inches

**Stem Socket Style:**

Gripneck-open type

**Wheel Bearing Type:**

Plain, self-lubricated

**Swivel Bearing Type:**

Annular ball

**Swivel Bearing Arrangement:**

Two row

**Stem Socket Depth:**

1.500 inches

**Stem Socket Diameter:**

0.375 inches

**Special Features:**

Nonstaining, nonmarking cushion treads, permanently bonded, impact resistant, hard rubber composition core; wheels tread thickness 3/16in.; wheel tread and core material hardness range hard rubber 75-85 shore d, soft rubber 70-85 shore a; tensile 1500 psi min., adhesion between tread and core is 50 lbs per inch of width; axles and stems - cold drawn steel, nut and bolt combination or solid rivet type and permanently fastened; ball bearings - corrosion resistant, case hardened ground steel, assembly with a water repellent grease

**Style Designator:**

Swivel offset

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A25600