

View Online at <https://aerobasegroup.com/nsn/5340-00-081-7054>

**Thread Class:**

3b rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

1.570 inches rod connection and 1.630 inches rod connection

**Shank Length:**

1.500 inches

**Hole Diameter:**

Between 0.374 inches and 0.376 inches

**Shank Diameter:**

Between 0.490 inches and 0.510 inches

**Width Across Flats:**

Between 0.740 inches and 0.760 inches

**Overall Height:**

Between 0.740 inches and 0.760 inches

**Overall Width:**

Between 0.475 inches and 0.520 inches

**Fork Span Width:**

Between 0.195 inches and 0.200 inches

**Securing Pin Hole Diameter:**

Between 0.045 inches and 0.051 inches

**Distance From Center Of Securing Pin Hole To Rod End:**

Between 0.490 inches and 0.510 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

2.385 inches

**Fork Arm Thickness:**

Between 0.140 inches and 0.160 inches

**Fork Depth:**

0.565 inches

**Thread Size:**

0.312 inches rod connection

**Material:**

Steel comp 4130 or steel comp 4140

**Material Specification:**

Mil-s-6758, cond c4 military specification 1st material response or mil-s-5626, cond c4 military specification 2nd material response

**Surface Treatment:**

Chromate zinc

**Surface Treatment Specification:**

299-099-031, pzg1, bell helicopter co mfr ref single treatment response

**Style Designator:**

Clevis

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A264a0

**Mil-std (military Standard):**

Mil-s-6758 spec.