

View Online at <https://aerobasegroup.com/nsn/5340-00-081-7054>

Thread Class:

3b rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

1.570 inches rod connection and 1.630 inches rod connection

Shank Length:

1.500 inches

Hole Diameter:

Between 0.374 inches and 0.376 inches

Shank Diameter:

Between 0.490 inches and 0.510 inches

Width Across Flats:

Between 0.740 inches and 0.760 inches

Overall Height:

Between 0.740 inches and 0.760 inches

Overall Width:

Between 0.475 inches and 0.520 inches

Fork Span Width:

Between 0.195 inches and 0.200 inches

Securing Pin Hole Diameter:

Between 0.045 inches and 0.051 inches

Distance From Center Of Securing Pin Hole To Rod End:

Between 0.490 inches and 0.510 inches

Distance From Pivot Pinhole Center To Rod Connection End:

2.385 inches

Fork Arm Thickness:

Between 0.140 inches and 0.160 inches

Fork Depth:

0.565 inches

Thread Size:

0.312 inches rod connection

Material:

Steel comp 4130 or steel comp 4140

Material Specification:

Mil-s-6758, cond c4 military specification 1st material response or mil-s-5626, cond c4 military specification 2nd material response

Surface Treatment:

Chromate zinc

Surface Treatment Specification:

299-099-031, pzg1, bell helicopter co mfr ref single treatment response

Style Designator:

Clevis

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A264a0

Mil-std (military Standard):

Mil-s-6758 spec.