

View Online at <https://aerobasegroup.com/nsn/5340-00-082-0036>

Fabrication Method (non-core):

Stamped

First Leg Length:

1.250 inches

Second Leg Length:

2.000 inches

Second Leg Width:

3.625 inches

First Leg Hole Diameter:

Between 0.312 inches and 0.328 inches

Second Leg Distance Between Hole Centers Along Width:

2.875 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.375 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.625 inches

Second Leg Slot Length:

0.625 inches

Second Leg Slot Width:

Between 0.312 inches and 0.328 inches

First Leg Thickness:

0.188 inches

Second Leg Thickness:

0.188 inches

First Leg Width:

3.625 inches

First Leg Distance Between Hole Centers Along Width:

2.875 inches

First Leg Distance From Edge To Hole Center Along Width:

0.375 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Second leg cutaway 1.563 deep by 2.125 wide 0.750 from each side and color green 24533

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200/8 federal specification single material response

Surface Treatment:

Enamel

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0